Pristup virtualnim poslužiteljima

- Protokol SSH
 Clinux
 Windows
- Protokol RDP

Project	~	Project / Compute / Instan	ICBS										
API Compute	Access	Instances											
0	verview							Insta	nce ID = 🗸		Filter	Launch Instance	Delete Instances
	Images	Displaying 5 items											
Ke	ey Pairs	Instance Name	Image Name	IP Address	Flavor	Key Pair	Status		Availability Zone	Task	Power State	Age	Actic
Server	Groups	•	centos-7	10.5.112.137	m1.medium		Active	=°	nova	None	Running	47 minutes	Cre
Volumes	>	centos-7-bio	centos-7	10.8.24.246	m1.xlarge	-	Active	÷	nova	None	Running	1 day, 5 ho	urs Cre
Network	>	centos-7	centos-7	161.53.133.228	m1.xlarge		Active	ı.	nova	None	Running	6 days, 3 h	ours
Data Processing	>	•	centos-7	161.53.133.195	m1.large	-	Active	-	nova	None	Running	1 week, 3 d	days Cre
Identity	>	•	centos-7	161.53.133.173	m1.xlarge		Active	=P	nova	None	Running	1 week, 3 d	lays Cre
		Displaying 5 items											

Nakon pokretanja virtualnog poslužitelja, možete dohvatiti IP adrese na upravljačkoj ploči Compute -> Instances

Pomoću protokola SSH i RDP spajate se na dodijeljenu IP adresu.

Protokol SSH

Za spajanje na virtualni poslužitelj potrebna je IP adresa posložitelja i korisničko ime. Korisničko ima je ime operativnog sustava npr. za CentOS→"centos", Ubuntu→"ubuntu" itd.

Linux

Ako koristite neki od Linux OS-a, virtualnom poslužitelju možete pristupiti iz komandne linije koristeći naredbu:

ssh OSposlužitelja@IPadresa

Windows

Ako koristite Windows OS, za pristup virtualnom poslužitelju potrebno je instalirati SSH klijent (npr. Putty).

Nakon instalacije i pokretanja, na početnom ekranu programa Putty, u polje Host Name (or IP address) potrebno je upisati:

OSposlužitelja@IPadresa

te zatim kliknuti na gumb Open.

🕵 PuTTY Configuration	? ×
Category:	
 Session Logging Terminal Keyboard Bell Features Window Appearance Behaviour Translation Selection Colours Connection Data Proxy Telnet Rlogin SSH Serial 	Basic options for your PuTTY session Specify the destination you want to connect to Host Name (or IP address) Port OSposlužitelja@IPadresa 22 Connection type: Raw Telnet Rlogin SSH Serjal Load, save or delete a stored session Saved Sessions Load Save Delete . Delete Delete . OSposlužitelja@IPadresa Save
<u>A</u> bout <u>H</u> elp	<u>O</u> pen <u>C</u> ancel

Protokol RDP

Prije spajanja na RDP potrebno se prijaviti preko konzole na upravljačkoj ploči i promijeniti lozinku.

Compute→Instances→Console

openstack.	🔲 adm	in •	
Project	· ·	Project / Compute / Instances / centos-7-bio	
Compute	Access		
0	verview	Overview Interfaces Loa Console Action Loa	
In	stances		
	Images	Instance Console	
K	ey Pairs	If console is not responding to keyboard input: click the grey status bar below. <u>Click here to show only console</u>	
Server	Groups	10 SAL DE DUSCEEN HIOUS, CICA DE DOWSETS DACK DUDDI.	
Volumes	>	Connected (encrypted) to: QEMU (instance 000001b2)	
Network	>		
Orchestration	>		
Data Processing	>		
Admin	>		
Identity	>		

Pritisnite Send CtrlAltDel, upišite korisničko ime Admin i lozinku koju ste ubacili kao meta podatak. Upišite novu lozinku.

Pokrenite Remote Desktop na vašem računalu

Dest match		
Best match		
App Remote Desktop Connection		
Apps		Remote Desktop Connection
Acrobat Reader DC	>	Арр
🔹 Registry Editor	>	
Recovery Drive	>	📑 Open
Search the web		· · · · · · · · · · · · · · · · · · ·
✓ re - See web results	>	Recent
Settings (4+)		-
Documents (1+)		5
		1
		1
		1

Unesite IPadresu i odaberite Connect

퉣 Remote	Desktop Connection	_	-		×	(
N	Remote Desktop Connection					
<u>C</u> omputer: User name: You will be as	IPadresa None specified sked for credentials when you con	nect.	~			
Show O	ptions	Connec	t	Ŀ	<u>l</u> elp	

Uneiste korisničko ime Admin i novu lozinku.

Nakon prvog pristupa pokrenite Windows Update i nadograditi operativni sustav. Windows OS ponekad za vrijeme nadogradnje prisilno restarta virtualno računalo pa je za vrijeme duljeg nesmetanog korištenja ili simulacije potrebno isključiti Windows Update. Korisnik je obavezan raditi sigurnosne nadogradnje virtualnog poslužitelja.